



IMINPods S acoustic booth - technical specification

Item	No.	Description
1	-	Intended use One person acoustic booth. Internal use only.
2	-	External dimensions [cm] H225, L105, W105
3	-	Construction Wooden, modular, timber-framed. Acoustic proof materials, sound-immersive elements, diffusers, bass trap, ESG safety glass
4	1	Touch-sensitive control panel Integrated motion sensor, touch-sensitive controller of colour temperature, illuminance and fan regulation (0-100%)
5	-	Finishing - interior Walls: acoustic panels with certified acoustic proof fabric, lacquered element (RAL or NCS palette) Ceiling: bass trap finished with acoustic proof fabric, LED linear lighting Floor: covering with sound dampening layer
6	-	Finishing Lacquered MDF (RAL or NCS palette), covered with transparent protective varnish
7	1	230V power supply Socket 2P+Z, 16A-250V
8	1	USB USB socket 230 V /5 V; 1500mA
9	1	RJ45 RJ45 socket CAT5E FTP
10	1	230V connection wire 3x1,5; lenght: 2,5m, plug 2P+Z, black
11	1	RJ45 connection wire FTP wire, lenght: 3,5m
12	1	12V power supply Plug adapter 12V, 4A, lenght - 2,5m
13	1	Ventilator Air flow: max 170 m3/h/pcs. Smooth regulation 0-100% Max. output: 5,4W, 0,45A (12V)
14	1	LED lighting Linear LED 11W, 200-1200 lm, 3000 - 6000K (controlled by touch-sensitive panel)
15	1	Motion sensor Integrated with touch-sensitive panel
16	1	Air inlet Working area: 72 cm2
17	1	Table [cm] L 90, H 95, W 9
18	1	Glass door + skylights Laminated glass (foil); 5+5mm (total thickness 11mm), safety tampered glass, CE certificate
19	-	Weight 320 kg net